



Prime Wrap

WHITE SHEATHING TAPE

DESCRIPTION: A thin, strong, durable white polypropylene film coated with an aggressive acrylic pressure sensitive adhesive (PSA) designed for use as a closure system and vapor seal on all interior and exterior sheathing materials. Prime Wrap Tape exceeds most building code requirements and can be used for new construction as well as repair on all vapor barrier materials.

FEATURES & BENEFITS:

- High performance sheathing tape installs and performs well over a wide temperature range
- Excellent vapor barrier tape on polyethylene film
- Performs well as a seam tape on extruded foam products such as Styrofoam and Foamular.
- Applies to Prime Wrap and all other major housewraps.
- Great for use as a sealing tape on DensGlass Gold and other sheathing brands

AVAILABLE SIZE:

- 1 7/8" X 55 YDS & 3" X 55 YDS standard
- Customs rolls available on request

TECHNICAL DATA

	<u>IMPERIAL</u>	<u>METRIC</u>
Thickness:	3 mils (0.003")	0.08 mm
Adhesion:		
Peel:	(oz/inch)	(N/25mm)
Polyethylene:	16.0	4.5
Stainless Steel:	45.0	12.5
Shear:	>24 hours @ 2.2 psi	>24 hours @ 15.2 kPa
Tensile:	20 lbs/inch	90.4 N/25mm
Elongation:	130%	130%
WVTR:	0.061 perms	
Temperature range:	-40°F to 185°F	-40°C to 85°C

IMPORTANT INFORMATION:

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties and are not intended to be used as specifications for defined applications. User must determine the product suitability for the end use application and assume all risks and liabilities. 2-2-09



IMPORTANT INFORMATION:

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties and are not intended to be used as specifications for defined applications. User must determine the product suitability for the end use application and assume all risks and liabilities. 2-2-09